

Eicher 333







Eicher 333



MODEL NAME/ NUMBER:	CONFIGURATION:
Engine	Simpson S 324
Cylinders	3
Cubic Capacity	2365 cc
Fuel Injection Pump	Inline
Clutch	Single
Transmission	Slinding mesh
No of speeds	8 Forward +2 Reverse
Tyres	6.00 x 16 Front, 12.4 x 28 Rear
Forward Speed @ rated rpm	27.71 kmph
PTO	Live
PTO Speed	555
Three point linkage and controls	Three point linkage with Automatic depth and draft control (ADDC)
	and diant control (ADDC)
Brakes	Dry disc brakes
Brakes Steering	500 1 500 1
	Dry disc brakes
Steering	Dry disc brakes Mechanical
Steering Electrical	Dry disc brakes Mechanical 12V,75 Ah
Steering Electrical Overall length	Dry disc brakes Mechanical 12V,75 Ah 3515 mm
Steering Electrical Overall length Overall width	Dry disc brakes Mechanical 12V,75 Ah 3515 mm 1650 mm
Steering Electrical Overall length Overall width Overall height	Dry disc brakes Mechanical 12V,75 Ah 3515 mm 1650 mm 2208 mm
Steering Electrical Overall length Overall width Overall height Wheel base	Dry disc brakes Mechanical 12V,75 Ah 3515 mm 1650 mm 2208 mm 1905 mm
Steering Electrical Overall length Overall width Overall height Wheel base Min. ground clearance	Dry disc brakes Mechanical 12V,75 Ah 3515 mm 1650 mm 2208 mm 1905 mm 355 mm
Steering Electrical Overall length Overall width Overall height Wheel base Min. ground clearance Min. turning circle radius	Dry disc brakes Mechanical 12V,75 Ah 3515 mm 1650 mm 2208 mm 1905 mm 355 mm 3000 mm
Steering Electrical Overall length Overall width Overall height Wheel base Min. ground clearance Min. turning circle radius Total Weight	Dry disc brakes Mechanical 12V,75 Ah 3515 mm 1650 mm 2208 mm 1905 mm 355 mm 3000 mm 1990 kg